



HP Color LaserJet CP 3525n (DK)(NO)(SE)

Tillverkare HP
 Artikelnummer 1429564
 Tillv artnr CC469A#BB2
 EAN 883585892426

6 701:-
 (exkl moms: 5 361:-)

Information

HP Color LaserJet CP 3525n printer with JetDirect and 250 sheet tray. (NO)(SV)(FI)(BALTIC)

Specifikation

Colour	Ja
Maximum resolution	600 x 1200 DPI
Economical printing	Optional automatic two-sided printing and N-up printing (saves paper)
Print speed (black, normal quality, A4)	30 ppm
Print speed (colour, normal quality, A4)	30 ppm
Time to first page (colour, normal)	As fast as 11 sec (from "ready")
Time to first page (black, normal)	As fast as 11 sec (from "ready")
Internal memory	256 MB

Memory slots	One DDR2-SDRAM 200-pin SODIMM slot
Processor	
Processor clock speed	515 MHz
Maximum internal memory	1 GB
Number of print cartridges	4 pcs
Maximum input capacity	sheets (75 g/m ² paper): 100; labels, transparencies, cardstock (163 g/m ²): 50 , cardstock (216 g/m ²): 30, envelopes: 10
Standard input capacity	850 sheets
Standard input trays	350 sheets
Maximum output capacity	2
Standard output capacity	250 sheets
Standard output capacity for transparencies	250 sheets
Standard media sizes	Up to 100 sheets
ISO A-series sizes (A0...A9)	A4, A5, B5 (JIS), envelopes (B5, C5, DL)
Envelopes sizes	A4, A5
JIS B-series sizes (B0...B9)	B5, C5, DL
Media size (tray 1)	B5
	Letter, legal, executive, 8.5 x 13, A4, A5, B5 (JIS), envelopes (No. 10, Monarch (7 3/4), C5, B5, DL), 98.4 x 148 to 215.9 x 355.6 mm

Media types supported	Paper (plain, light, bond, recycled, mid-weight, heavy, mid-weight glossy, heavy glossy, extra heavy, extra heavy glossy, cardstock, card glossy) colour transparency, labels, letterhead, envelope, preprinted, prepunched, coloured, rough, opaque film
Plain paper	Ja
Bond paper	Ja
Recycled paper	Ja
Envelopes	Ja
Labels	Ja
Transparencies	Ja
Card stock	Ja
Glossy paper	Ja
Maximum print size	207.4 x 347.1 mm
Media weight (tray 1)	60 to 216 g/m ² (plain paper), 105 to 220 g/m ² (glossy paper)
Duplex printing	Nej
Print technology	Laser
Interface	One embedded HP Jetdirect 10/100/1000 Base-T Ethernet port, one Hi-Speed USB 2.0 port, one available EIO slot
Network ready	Ja
Networking features	Via HP Jetdirect Gigabit Ethernet embedded print server: TCP/IP (IP Direct Mode; may require software from the NOS vendor or third-party vendor: LPD, FTP, IPP), IPX/SPX, DLC/LLC, AppleTalk, Auto-IP, Apple Bonjour-compatible, NDS, Bindery, NCP, Telnet, SLP, IGMP, BOOTP/DHCP, WINS, SNMP v 1, 2c, 3, HTTP HP Jetdirect Gigabit Ethernet embedded print server
Minimum system requirements	Windows Vista®: Intel® Pentium® II or Celeron® processor, Adobe® Acrobat® Reader 5, 512 MB RAM, 220 MB hard disk space, Microsoft® Internet Explorer 7, CD-ROM drive; USB port; Microsoft® Windows® 2000, XP, Server 2003 Server 2008: Intel® Pentium® II or Celeron® processor, Adobe® Acrobat® Reader 5, 256 MB RAM, 220 MB hard disk space, Microsoft® Internet Explorer 6, CD-ROM drive, USB port

Compatible operating systems	Microsoft® Windows® 2000, XP Professional, Server 2003, Server 2008 Windows Vista®; Mac OS X v10.3, v10.4, v10.5
Dimensions W x D x H	514 x 491 x 358 mm
Weight	32.9 kg
Printing colours	4 CMYB
Bundled software	Software for Microsoft® Windows®: Desktop SureSupply, HP Update Macintosh: HP Postscript 3 driver software (v4.3.1) and HP Printer Utility for Mac OS X
Package dimensions (W x D x H)	75.4 x 59.9 x 53.1 cm (29.7 x 23.6 x 20.9 ")
Product dimensions when open (LxWxD)	82.3 x 73.9 x 35.8 cm (32.4 x 29.1 x 14.1 ")
Print quality (black, normal quality)	600 x 600 DPI
Print quality (colour, best quality)	1200 x 600 DPI
Print quality (black, best quality)	1200x600 DPI
Print speed (colour, best quality, A4)	Up to 30 ppm
Print speed (black, best quality, A4)	Up to 30 ppm
Memory upgrade	Expandable up to 1024 MB through one industry-standard DIMM slot
Memory technology	NANDFlash, DDR2 SDRAM
Input capacity for envelopes (primary tray)	10 sheets
Duty cycle (maximum)	1500 to 5000 Up to 75000 pages
Standard output capacity for envelopes	10 sheets

Custom media sizes	Multipurpose tray: 98 x 148 to 216 x 356 mm; 250-sheet input tray: 148 x 210 to 216 x 297 mm; optional 500-sheet input tray: 148 x 210 to 216 x 356 mm
Media size (tray 3)	A4, A5, B5 (JIS), executive, 148 x 210 to 215.9 x 355.6 mm
Duplex supported media size	A4, A5, B5 (JIS)
Media size (tray 2)	Letter, executive, A4, A5, B5 (JIS), 148 x 210 to 215.9 x 297 mm
Media handling	Sheetfed
Media type and capacity (tray 2)	sheets (75 g/m ² paper): 250, cardstock (163 g/m ²): 100, transparencies: 100
Media type and capacity (tray 3)	sheets (75 g/m ² paper): 500, cardstock (163 g/m ²); labels, transparencies : 200, glossy media with adapter (220 g/m ² , 10 x 15 cm): 100
Media weights by paper path	Multipurpose tray: 60 to 216 g/m ² (plain paper), 105 to 220 g/m ² (gloss y paper); 250-sheet input tray: 60 to 163 g/m ² (plain paper), 105 to 220 g/m
Recommended media weight	60 to 220 g/m ²
Paper handling	100-sheet multipurpose tray, 250-sheet input tray, Optional 500-sheet input tray, 250-sheet top output bin
Maximum paper trays	3
Media weight (tray 3)	60 to 176 g/m ² (plain paper), 105 to 220 g/m ² (glossy paper) (CP3525x)
Duplex supported media weight	60 to 163 g/m ² (automatic), 60 to 220 g/m ² (manual)
Media weight (tray 2)	60 to 163 g/m ² (plain paper), 105 to 220 g/m ² (glossy paper)
Paper handling optional/input	Optional 500-sheet paper and Heavy/Glossy media input tray
Paper handling standard/input	100-sheet multipurpose tray, 250-sheet input tray
Paper handling standard/output	250-sheet top output bin
Print margin bottom (A4)	2 mm absolute/5 mm assured image

Print margin left (A4)	2 mm absolute/5 mm assured image
Print margin right (A4)	2 mm absolute/5 mm assured image
Print margin top (A4)	2 mm absolute/5 mm assured image
Typefaces	80 HP font set (plus Greek, Hebrew, Cyrillic, Arabic)
Standard printer languages	HP PCL 6, HP PCL 5c, HP Postscript level 3 emulation, direct PDF printing v 1.4
Printer management	HP Web Jetadmin, HP Easy Printer Care Software, HP Sure Supply, HP Colour Access Controls, HP Embedded Web Server
Duplex print options	Manual (driver support provided)
Print technology resolution	HP ImageREt 3600 DPI
I/O ports	1 USB-B, 1 10/100/1000 Base-T Ethernet
Optional connectivity	Via one open EIO slot: 802.11b/g wireless LAN (J8007G - HP Jetdirect 690n IPv6/IPSec 802.11g Wireless Print Server), IPSec (J7961G - HP Jetdirect 635n IPv6/IPsec Print Server), other networking accessories
Minimum system requirements for Macintosh	Mac OS X v10.3, v10.4, v10.5; PowerPC G3, G4, G5 or Intel® Core
Acoustic power emissions	6.9 B(A) (active/printing), 4.6 B(A) (ready)
Acoustic pressure emissions	54 dB(A) (active/printing), 33 dB(A) (ready)
Energy Star certified	No
Power requirements	Input voltage: 115 to 127 V ac (+/- 10%), 60 Hz (+/- 2 Hz), 12 A; 220 to 240 V ac (+/- 10%), 50 Hz (+/- 2 Hz), 6 A
Power consumption	643 watts (active/printing), 60 watts (ready), 35.1 watts (sleep 1), 10 watts (sleep 2), 0.48 watts (off); Typical Electricity Consumption (TEC): 4.212 kWhr/Week*
Power consumption (PowerSave)	Sleep 1: 35.1 watts, sleep 2: 10 watts
Power consumption (off)	0.48 watts

Power consumption (standby)	643 watts
Maximum dimensions (W x D x H)	822 x 739 x 358 mm
Recommended humidity operating range	20 to 60% RH
Operating relative humidity range	10-70 %
Recommended operating temperature range (T-T)	15 to 27° C
Storage temperature range (T-T)	0-35 °C
Package weight	39 kg
Operating temperature range (T-T)	10 - 30 °C
Storage relative humidity range	10-90 %
Safety	IEC 60950-1 (International), EN 60950-1+A11 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries
Print speed (black, normal quality, US letter)	30 ppm
Print speed (colour, normal quality, US letter)	30 ppm
First page out (black&white, A4, ready)	As fast as 11 sec

First page out (black&white, letter, ready)	11 s
Source data-sheet	ICEcat.biz
Electromagnetic compatibility	CISPR 22: 2005/EN 55022: 2006 Class B, EN 61000-3-2: 2000+A2, EN 61000-3-3: 1995+A1, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class B (USA), ICES-003, Issue 4, (Canada), GB9254-1998, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries
Driver updates	For a list of printer drivers and updated HP printer software go to http://go/cljcp3525_software
Control panel	4-line graphical colour display, 3 lights (Attention, Data, Ready), 7 buttons (Help, Menu, OK, Stop, Back, Down, Up)
Upgrade type	Color tables, formatter firmware, software drivers
First page out (colour, A4, ready)	As fast as 11 sec